



# ORION-INT-RS232

## Orion Repeater Interface

The ORION-INT-RS232 interface module allows GFE's ORION Conventional Panels to be interfaced to ORION MINI-REPS and ORION REPS using a 4-core data communication cable suitable for serial data transmission.

This interface is compatible with the following panels and repeaters:

- ▶ ORION Conventional Panel 2, 4 and 8 zones - version 1.5 and above
- ▶ ORION REP and ORION MINI-REP

The maximum distance between panel and repeater is 100m.

+38 (044) 221-49-11

+38 (067) 382-52-31

support@dig.in.ua

### TECHNICAL SPECIFICATIONS

|                                   |  |
|-----------------------------------|--|
| SUPPLY VOLTAGE                    | 28 V DC nominal - range 17 to 30 V DC  |
| SUPPLY CURRENT                    | 5 mA   |
| SOFTWARE & HARDWARE COMPATIBILITY | ORION Conventional Panel-version 1.5 and above<br>ORION MINI-REP and ORION REP |
| MAX. HUMIDITY                     | 95% RH Non-Condensing  |
| OPERATING TEMPERATURE             | -10°C to 50°C  |
| DIMENSIONS                        | 100.3 (L) x 35 (W) x 18 (H) mm   |
| WEIGHT                            | 20 g   |
| <b>ORDER CODE</b>                 |  |
| <b>ORION-INT-RS232</b>            | ORION RS232 REPEATER INTERFACE   |